



## NANO ACTION

THE HEAT PUMP DEDICATED TO SMALL POOLS



### MAIN FEATURES

Plug & Play

For pools up to 35m<sup>3</sup>

Compatible with all above ground pools

Ultra compact

**The heat pump special swimming pools up to 35 m<sup>3</sup>.**

Specifically designed to make life easier, the Nano Action comes equipped with 32/38 mm connectors for a quick connection to any classical filtration system.

Simply plug in your heat pump and let your swimming pool get warm.

Designed with the same specifications as a premium heat pump, the Nano Action features high efficiency in an ultra compact shell, and its light weight enables anyone to store it away once the season is over.

### WARRANTIES

Heat Pump **2years**

Compressor **5years**

Titanium coil  
anti corrosion warranty **15years**

\* Average Coefficient of performance according to European standards (Air 26 °C, Water 26 °C, Hygro 80 %)  
TÜV Certified  
\*\* Average noise 10 m from the heat pump



## ADVANTAGES

- Easy to install thanks to its Plug & Play system
- Compatible all above ground pools, wooden pools and in ground pools (<35m<sup>3</sup>)
- Light and easy to move
- Operates from 8°C
- Connects to a standard electric plug

## PLUG & PLAY



## COMPATIBLE WITH ALL SWIMMING POOLS



Pooler



Reinforced printed Packaging



Multi-language user manual

## ACCESSORIES INCLUDED



PVC connectors  
Ø 32-38mm



5m electric extension with  
10 mA earth leakage protection

E.U. STANDARD  
TÜV CERTIFIED

Data based on French territory and provided for informational purposes only and may change without notice.

Swimming pool volume		from 10 to 21 m <sup>3</sup>	from 15 to 28 m <sup>3</sup>	from 20 to 35 m <sup>3</sup>
Reference: PC-NANO-		A3	A4	A5
Air 26°C	Max. power output (W)	3,010	4,200	5,010
Water 26°C	Power consumption (W)	540	760	910
Hygro 80%	COP	5.61	5.50	5.50
Air 15°C	Max. power output (W)	2,210	3,100	4,030
Water 26°C	Power consumption (W)	490	690	900
Hygro 70%	COP	4.51	4.50	4.50
Power supply		Mono 230V / 50Hz		
Max. power (W)		930	1 200	1 500
Heating temp. range		15°C / 40°C		
Operating range		8°C / 43°C		
Flow (m <sup>3</sup> /h)		1.3	2	2.5
Refrigerant		R32		
Packaging dimensions (mm)		460 x 370 x 415		
Dimensions (mm)		400 x 280 x 385		
Net/Gross weight (kg)		18 / 20	24 / 28	26 / 30
Noise level at 1 m (dB(A))		<53	<55	<56
Noise level at 10 m (dB(A))		<32	<35	<36
Compressor type		Rotary		
Compressor brand		Toshiba		
Heat exchanger		Twisted Tech® Titanium		
Function		Heating		
Load losses (mCE)		0.8		